







HSM Powerline FA 400.2

HSM Powerline FA 400.2

Mobile, top of the range model for use in archives. Also suitable for shredding CDs and floppy disks. The sturdy technology has been especially designed for a large throughput and long total operating time. Integrated, manual oiler for cutting unit (particle cut version only). Material intake via loading table and electric conveyor belt. Stand-by mode with LED indicator. Keypad control for constant operation and reverse. Stops automatically when the collection container is full or has been removed. Auto reverse in the event of paper jam. Mobile trolley with very sturdy, reusable waste bag included with the standard equipment. Made in Germany.

Product type description	HSM Powerline FA 400.2 5,8mm	HSM Powerline FA 400.2 5,8x50mm
Order number	1513144	1514144
EAN Code	4026631020800	4026631020824
Shredder material		
Cutting type	strip cut	particle cut
Security level new (DIN 66399)	P-2 / O-2 / T-2 / E-2	P-3 / O-2 / T-3 / E-2
Security level old (DIN 32757-1)	2	3
Cutting width	5.8 mm	5.8 mm
Particle length	0 mm	50,00 mm
Cutting capacity (70g/m ²)	130 sheet	120 sheet
Cutting capacity (80g/m ²)	104 sheet	96 sheet
Intake width	428 mm	428 mm
Container volume	460 l	460 l
Cutting speed	220 mm/s	220 mm/s
Noise level (idle operation)	61 dB	61 dB
eclass 5.1	24320704	24320704
UN/SPSC	44101603	44101603
Power consumption of the motor	4000 W	4000 W
Voltage	400 V	400 V
Frequency	50 Hz	50 Hz
Warranty period (months)	12	12
Depth	1568 mm	1568 mm
Width	1157 mm	1157 mm
Height	1650 mm	1650 mm
Weight	425 kg	425 kg

HSM Powerline FA 400.2

Product type description	HSM FA 400.2 3,9x40mm	HSM Powerline FA 400.2 11,8mm
Order number	1515144	1534144
EAN Code	4026631043519	4026631020848
Shredder material		
Cutting type	particle cut	strip cut
Security level new (DIN 66399)	P-4 / O-3 / T-4 / E-3 / F-1	P-1 / O-1 / T-1 / E-1
Security level old (DIN 32757-1)	3	1
Cutting width	3.9 mm	11.8 mm
Particle length	40,00 mm	
Cutting capacity (70g/m ²)	95 -100 sheet	180 sheet
Cutting capacity (80g/m ²)	80-85 sheet	144 sheet
Intake width	428 mm	428 mm
Container volume	460 l	460 l
Cutting speed	220 mm/s	210 mm/s
Noise level (idle operation)	61 dB	61 dB
eclass 5.1	24320704	24320704
UN/SPSC	44101603	44101603
Power consumption of the motor	4000 W	4000 W
Voltage	400 V	400 V
Frequency	50 Hz	50 Hz
Warranty period (months)	12	12
Depth	1568 mm	1568 mm
Width	1157 mm	1157 mm
Height	1650 mm	1650 mm
Weight	425 kg	425 kg